

HAND PUMPS

Haven hand pumps are rugged, lightweight, compact and easy to use. Ideal as a self contained pressure source for calibration of gauges and switches and compatible with Haven hand-held calibrators.

All models feature a precision vernier for fine adjustment and pressure release valve. Additional hose kits and adaptors are available.



H-TP1



H-LTP1



PP300, PPD25300 & HP3000

SPECIFICATIONS	PP300	PPD25300	HP3000	H-LTP1	H-TP1
PRESSURE RANGE(S)	0-300psi (20 Bar)	Pressure 0-300psi (20 Bar) Vacuum 0-25"Hg (850 mBar)	0-3000 psi (200 Bar)	Pressure 0-30psi (2 Bar) Vacuum 0-24"Hg (800 mbar)	Pressure 0-360psi (25 Bar) Vacuum 0-24"Hg (800 mbar)
WEIGHT	0.6 Kg	0.65 Kg	0.8 Kg	0.6 Kg (pump only)	0.51 Kg
PHYSICAL DIMENSIONS	230x130x80 mm	250x130x80 mm	280x130x80 mm	170x46 mm (DIA)	220x105x63 mm
TEST CONNECTIONS	¼" NPT Female	¼" NPT Female	¼" NPT Female	Two push fit connectors to take 4mm flexible hoses with ¼" BSP female adaptors	3/8" BSP Female (master instruments) ¼" BSP Female (adaptors)
MATERIALS OF CONSTRUCTION	Machined aluminium body stainless steel shaft and needle valve, ABS plastic handles, brass tee and connector			Bright nickel plated brass, clear anodised aluminium	
HOSE	Nylon	Nylon	Nylon With Braided Metal Covering	Nylon	Nylon
SEALS	Viton	Viton	Ethylene Propylene	Nylon	Nylon

JCB Instruments Pty Ltd

PO Box 262 497 Wentworth Avenue Toongabbie NSW Australia 2146
Ph. 612 9896 8833 Fax. 612 9896 8500 Email: sales@jcbinst.com.au
Web: www.jcbinst.com.au